

SCP PART#: LUTRON-QS-P

Composite Cable

UNSH 2/C 16/19 SBC 0.010" Plenum INS Black & Red Colors,
 SHLD 2/C 22/7 SBC 0.015" FFEP INS Purple & White, O/A SHIELD & 24/7
 STC Drain; FOIL & Drain Facing in & O/A MYLAR & 0.025" PVC FT6 Plenum JKT

Conductor : Unsh 2/C 16/19 & SHLD 2/C 22/7 Bare Copper	
Cable & Spool Weight: 10 kgs/500ft	Final Diameter : 0.300 inches
Insulation : Plenum	Jacket : 0.025" Plenum
Approvals : UL OR C(UL) CMP (UL) CL3P	

Print Notes : Sequentially marked per 2FT (0 - infinity)
 Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N LUTRON-QS-P - - - 2/C 22 AWG
 BC STRANDED SHIELDED W/DRAIN + 2/C 16 AWG BC STRANDED - - -
 E198134-SCP (UL) OR C(UL) CMP (UL) CL3P 75°C - - - CE EU ROHS EC P§
 - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 ROHS

75 degrees Celsius and 300V Cable Rated
 Total Cable Weight : 65 kg/km
 Spool Dimension: 12x12" Plywood

UNSH 2/C 16/19 Bare Copper
 DC Resistance 25°C: 4.13 Ohms/1000'
 Mutual Capacitance: 21.7 pF/ft
 Impedance: 70 Ohms
 Velocity of Prop: 75%
 Inductance: 1.2 mH/km

SH. 2/C 22/7 Bare Copper
 DC Resistance 25°C: 15.0 Ohms/1000'
 Mutual Capacitance: 46.8 pF/ft
 Shield Capacitance: 84.7 pF/ft
 Velocity of Prop: 70%
 Inductance: 1.3 mH/km

(All of the above values are approximated to within +/-10%)